

<b>TECHNICAL CHARACTERISTICS</b>		
Width x depth x height	(mm)	200 x 560 x 590
Weight	(kg)	17
Sound level	(db (A))	< 70
membrane	(n°)	1
Activated carbon filter		
<b>SUPPLY WATER CHARACTERISTICS</b>		
Type of water		Drinkable
Minimum water temperature	(°C)	5
Maximum water temperature	(°C)	45
Minimum supply flow rate	lit/hr	700
Maximum supply pressure	(bar)	3.5
Minimum supply pressure	(bar)	1
<b>OPERATING ENVIRONMENT</b>		
Maximum relative humidity	(%)	90
Minimum air temperature	(°C)	3
Maximum air temperature	(°C)	40
<b>ELECTRICAL CHARACTERISTICS</b>		
Supply type		Single-phase + earth
Voltage rating	(V)	230
Frequency	(Hz)	50
Power	(W)	186
Circuit board protection fuse type		
<b>PERMEATE CHARACTERISTICS</b>		
Maximum flow at 15°C	lit/hr	approx. 150
Permate/concentrate production ratio		approx. 1:1.5
<b>REPLACEMENT CONDITIONS</b>		
Activated carbon filter	(l)	12,000
Reverse osmosis membrane		When blocked