



60 x 80

Modello - Model - Model - Gerätetyp	AE68X2500	AE68X2510
EVOLVE PA		
Descrizione - Description - Description - Beschreibung	PA 60x80 TN	PA 60x80 BT
Range	-2°C +8°C	-20°C -10°C
Funzionamento - Operating Mode - Mode de fonctionnemen - Betriebsmodus V = Ventilato - Ventilated - Ventilé - Umluftkühlung	V	V
Capacità lorda - Gross Capacity - Capacité brute - Bruttovolumen	750	750
Materiale Esterno - External Material - Matériau Extérieur - Werkstoff Außen	304	
Dimensioni esterne - External Dimension - Dimensions externes - außenabmessungen		
Lunghezza - Width -Largeur - Breite	790	790
Profondità / con porte aperte - Depth / with open doors Profondeur avec portes ouverte - Tiefe/mit geöffneter Tür	1000/1723,5	1000/1723,5
Altezza - Height - Hauteur - Höhe	2025	2025
Materiale Interno - Internal Material - Matériau Intérieur - Werkstoff Innen	304	
Dimensioni interne - Internal Dimension - Dimensions internes - Innenabmessungen		
Lunghezza - Width -Largeur - Breite	640	640
Profondità - Depth - Profondeur - Tiefe	862,5	862,5
Altezza - Height - Hauteur - Höhe	1390	1390
Porte - Doors - Portes - Türen	1, Full	1, Full
Dotazione Standard - Standard Equipment - Equipement standard - Standardausstattung	20 coppie guide - 20 pairs of slides 20 glissieres - 20 paar führungen	
Capacità teglie - Pans capacity MAX - Capacité bacs - Backblechekapazität	n°27 600x800	n°27 600x800
Interasse teglie - Pans pitch - Pas des bacs - Backblecheabsatz	50	50
Luce interna - Internal light - Eclairage intérieure - Innerbeleuchtung	●	●
Serratura - Lock - Serrure - Schloss	●	●
Sbrinamento - Defrost - Dégivrages - Abtauen		
Type	Hot Gas	Hot Gas
N° Defrost in 24 hrs.	INTELLI	INTELLI
Evaporazione acqua sbrin. - Evaporation of defrost water - Evaporation eau de dégivrage - Tauwasserverdunstung	Automatic by Hot Gas	Automatic by Hot Gas
Compressor	embraco	
Model	EMT6165U	NT2170U
Potenza - Power - Puissance - Leistung	HP 1/3	1
T° Evaporation	°C -10	-30
Potenza frigorifera - Refrigerant Power - Puissance frigorifique - Kälteleistung	watt 520	650
Refrigerante - Refrigerant type - Réfrigérant type - Kältemitteltyp	GWP R290 / 3	R290 / 3
Quantità di refrigerante - Refrigerant quantity - Quantité de réfrigérant - Kältemittelmenge	gr 90	130
Potenza assorbita - Total Power - Puissance - Leistung	watt 330W 2,1A / 350W 2,3A	700W 3,5A / 940W 4,7A
Tensione alimentazione - Supply Voltage - Tension d'alimentation - Anschlussspannung	V 230V~ 50Hz	230V~ 50Hz
Noise Level	dbA 53	58
Peso Netto - Net weight - Poids net - Netto Gewicht	kg 152	152
Versione Predisposta - Remote version - Version sans groupe - Modelle ohne Aggregat Sbrinamento elettrico - Electrical defrosting - Dégivrage électrique - Elektrische Abtauerung	□	□
Efficienza Energetica - Energy Efficiency - Classe Énergie - Energieeffizienzklasse	C	D
Energia - Energy - Énergie - Energie	kWh / annum 751	2777
Volume Netto - Net Volume - Volume Net - Nettoinhalt	l 648	648
Classe Climatica - Climate Class - Classe Climatique - Klima Klasse	5 40°C-40%	5 40°C-40%

● = Dotazione di serie - Standard equipment - Dotation standard - Serien Ausstattung □ = Optional