

A B
A B
A B
A B
TN TB TB/TN TC TC/TN N  
 Chiller Freezer Dual Temp Heated Hot&Cold Non-refrigerated

RS - Static  
 RV - Ventilated  
 RS/TC S - Static and Dry Heat convertible  
 RV/TC S - Ventilated / Dry Heat convertible  
 HUR - Meat  
 CH - Chocolate  
 TC S - Dry Heat  
 TC BM - Bainmarie  
 N - Non-refrigerated

<b>H</b> 2000	2000	2000	2000
<b>D</b> 700	700	700	700
<b>L</b> 937	1250	1875	2500

**3M1** sandwiches • dairy • drinks • delicatessen • fresh products

**Installation**  
• Plug in

**Configuration**  
5 adjustable shelves  
Depth 250mm  
**Temperature range**  
-1/+5°C

**Refrigerant**  
R290

**Refrigeration**  
Ventilated

**Compressor**  
Hermetic

**Climate & product class**  
3M1

**Side panels**  
25mm

**Closing system**  
Swing doors (tempered double glass  
4+10+4mm)

**Lighting**  
Optional (canopy and shelves)

**Equipment handling**  
Adjustable feet

**Defrost**  
Air



External dimensions (LxDxH)	Sides 25mm thick	Adjustable feet	987x700x2000mm	1300x700x2000mm	1925x700x2000mm	2550x700x2000mm
		Swivel casters				
	Sides / thick	Adjustable feet				
		Swivel casters				
<b>Net volume</b>			263,1l dm3	351,00 dm3	526,50 dm3	702,00 dm3
<b>Weight (net)</b>			173 kg	231 kg	347 kg	463 kg
<b>Refrigeration</b>	Ventilated					
<b>Refrigerant</b>	R290					
<b>Climate class</b>	3					
<b>Operating conditions</b>	25 °C / 60 %RH					
<b>Product temperature</b>	-1/+5°C					
<b>Compressor (q.ty-type)</b>	1 Hermetic	1 Hermetic	1 Hermetic	1 Hermetic	1 Hermetic	1 Hermetic
<b>Defrost</b>	Air					
<b>Power supply</b>	230 V / 1 Ph / 50 Hz					
<b>Electrical input (nominal)</b>	584 W/ 2.86 A	601 W/ 2.94 A	649 W/ 3.18 A	783 W/ 3.84 A		
<b>Electrical input (defrost)</b>	0 W/ 0 A	0 W/ 0 A	0 W/ 0 A	0 W/ 0 A		

Technical sheet about models with condensing unit included with air / el. heater

**Setup**

Shelves dimensions (LxD)	930x250mm	1240x250mm	2pcx930x250mm	2pcx1240x250mm
	930x250mm	1240x250mm	2pcx930x250mm	2pcx1240x250mm
930x250mm	1240x250mm	2pcx930x250mm	2pcx1240x250mm	
930x250mm	1240x250mm	2pcx930x250mm	2pcx1240x250mm	
930x250mm	1240x250mm	2pcx930x250mm	2pcx1240x250mm	

Height	Length	Model type	Total display area (m2)	Temperature class	Recommended temperature (°C)	Energy class	Energy efficiency index EEI	Annual energy consumption kWh/A	Light source type and class
2000	937mm	Vertical	1,51	M1	+1°C	B	18,17	1918,80	/
	1250mm	Vertical	2,02	M1	+1°C	B	15,55	1972,64	/
	1875mm	Vertical	3,03	M1	+1°C	B	12,60	2132,79	/
	2500mm	Vertical	4,04	M1	+1°C	B	12,15	2572,16	/

Configuration: Vertical refrigerated show case plug in, closed with swing doors with five shelves defrosting-air

